




# Hose reel HM 710

# EBINGER

Technisches Equipment



- Security Handle-System that allows the handle to stay in the place, avoiding the rotation during the manual hose unreeling
- Sturdy drum
- Casing in painted steel or stainless steel
- Adjustable rewinding break
- Stable mounting bracket
- Drum supporting brushings made from TENAXID
- Max. 200m hose, max. 1" hose



| Medium            | Casing                           | Length of the hose | Max. pressure | Max. temp. | swivel          | Swivel connection | Item-No.               |
|-------------------|----------------------------------|--------------------|---------------|------------|-----------------|-------------------|------------------------|
| Water - air       | painted steel<br>stainless steel | without hose       | 20bar         | 90°C       | brass           | ½" F              | 8.710.100<br>8.714.100 |
|                   | painted steel<br>stainless steel | without hose       | 20bar         | 90°C       | brass           | 1" F              | 8.710.130<br>8.714.130 |
| High pressure 100 | painted steel<br>stainless steel | without hose       | 100bar        | 130°C      | stainless steel | ½" F              | 8.710.200<br>8.714.200 |
|                   | painted steel<br>stainless steel | without hose       | 100bar        | 130°C      | stainless steel | 1" F              | 8.710.230<br>8.714.230 |
| High pressure 200 | painted steel<br>stainless steel | without hose       | 200bar        | 130°C      | stainless steel | ¾" F              | 8.710.300<br>8.714.300 |
| High pressure 400 | painted steel<br>stainless steel | without hose       | 400bar        | 130°C      | stainless steel | ¾" F              | 8.710.400<br>8.714.400 |
| Oil               | painted steel                    | without hose       | 150bar        | 60°C       | steel zined     | ½" F              | 8.710.900              |
|                   | painted steel                    | without hose       | 150bar        | 60°C       | steel zined     | 1" F              | 8.710.930              |
| Grease            | painted steel<br>stainless steel | without hose       | 600bar        | 60°C       | steel zined     | ¾" F              | 8.714.500<br>8.714.500 |
| Diesel            | painted steel<br>stainless steel | without hose       | 10bar         | -          | brass           | 1" F              | 8.714.130<br>8.714.130 |

| outer Ø |      | length    |
|---------|------|-----------|
| ¼"      | 14mm | Max. 200m |
| ⅜"      | 17mm | Max. 120m |
| ½"      | 20mm | Max. 85m  |
| ⅝"      | 21mm | Max. 60m  |
| ¾"      | 27mm | Max. 45m  |
| 1"      | 34mm | Max. 30m  |

# EBINGER

Technisches Equipment

**Ebinger GmbH**  
Edesheimer Straße 51  
D-76835 Rhodt /  
Germany

Fon +49 (0)6323-937 465-0  
Fax +49 (0)6323-937 465-20

info@ebinger-gmbh.com  
www.ebinger-gmbh.com

